PRODUCT

SUMMARY

INFORMATION

Series



| Ref. | EAN | Finish |
|-------------|---------------|--------------|
| GPU010/AC | 8435668058780 | ACERO S.316 |
| GPU010/ANG | 8435668058797 | NEGRO MATE |
| GPU010/AAO | 8435668058803 | AZUL OCEANO |
| GPU010/ACL | 8435668058810 | ROSA CORAL |
| GPU010/AMK | 8435668058827 | МОКА |
| GPU010/AGCB | 8435668058834 | GRIS COBALTO |

| NAME | MATERIAL | REF |
|-------------------------------|--|---|
| Ø50mm shower head | SUS 316 | |
| upper pipe | SUS 316 | |
| 6mm*8mm screw | SUS 304 | |
| faucet body | SUS 316 | |
| MINGRUI HQ2118 cartridge | assembly | Ø23.5MM |
| handle | SUS 316 | |
| screw | SUS 304 | |
| color button | NBR | |
| 36*3.2mm rubber | NBR | |
| down pipe | SUS 316 | |
| Ø160mm cover plate(50mm hole) | SUS 316 | |
| Ø152mm flxed seat(50mm hole) | SUS 316 | |
| screw | SUS 304 | |
| 1.3m*Ø14mm G1/2 inlet pipe | SUS 316 | |
| G1/2 elbow connection | SUS 316 | |
| | Ø50mm shower head upper pipe 6mm*8mm screw faucet body MINGRUI HQ2118 cartridge handle screw color button 36*3.2mm rubber down pipe Ø160mm cover plate(50mm hole) Ø152mm fixed seat(50mm hole) screw 1.3m*Ø14mm G1/2 inlet pipe | Ø50mm shower head SUS 316 upper pipe SUS 316 6mm*8mm screw SUS 304 faucet body SUS 316 MINGRU HQ2118 cartridge assembly handle SUS 316 screw SUS 304 color button NBR down pipe NBR Ø160mm cover plate(50mm hole) SUS 316 Ø152mm fixed seat(50mm hole) SUS 316 screw SUS 304 1.3m*Ø14mm G1/2 inlet pipe SUS 316 |

| Installing instruction | | |
|--|--------------------------------|--|
| 15mm embedded Step 1.Embedd water pipe underground | Step 2.Connect the inlet pipe | |
| Step 3.Tighten the screws | Step 4.Close the cover | |
| Step 5.Connect the faucet body with the pipes | Step 6.Connect the shower head | |

UTAHSeries

POOLIMEX


UTAH Series **POOLIMEX**


UTAHSeries

POOLIMEX

FLOW RATE

| Detalles | |
|--------------------------|--------|
| FLOW RATE REF | GPU010 |
| Top shower 0.1Mpa(L/MIN) | 4.7 |
| Top shower 0.3Mpa(L/MIN) | 13.7 |
| Top shower 0.5Mpa(L/MIN) | 19.4 |





| Product sizes (cm) | 126.5*53.7*10.7 |
|-------------------------|-----------------|
| Weight (kg) | 8.5 |
| Guarantee | 10 years |
| Max Preassure (bar) | 8 |
| Min Preassure (bar) | 1 |
| Optimum preassure (bar) | 3-4 |
| Max. temperature | 55 °C |
| Min temperature | 0 °C |

CERTIFIES

That all our products, provided that they are used in normal conditions or installed in accordance with current standards, are guaranteed against any manufacturing defect for a period of five years, except for products purchased before January 1, 2020, which will have the mand atory coverage of 2 years from the date of invoice.

Requirements and exclusions

Failure to comply with the instructions for assembly, use and maintenance of our products on the packaging and in our catalogue and published on our website: www.imexproducts.es, releases IMEX PRODUCTS, S.L. from any liability.

In any case, the acceptance of the defect by our technical department is necessary. In addition, transport costs will be charged only in the event that on IMEX PRODUCTS, S.L. technician determines the proper functioning of our products.

IMEX PRODUCTS, S.L. will decide to repair the product or replace it. It will be necessary to present the purchase invoice.

Assemnly, maintenance or repairs carried out by non-specoalists re excluded from the warranty.

Wearing parts such as hoses, handles, seals, filters, aerators, etc. are not covered by the warranty.

